
Jovian

Aakash N S, Siddhant Ujjain

Mar 11, 2020

GETTING STARTED

1	Installation	3
2	Uploading Jupyter Notebooks to Jovian	5
2.1	Uploading Notebooks	5
2.2	Benefits of Jovian	5
3	Reproducing uploaded notebooks	7
3.1	Clone	7
3.2	Install	7
3.3	Pull	8
4	Notebook versioning and diffs	9
4.1	Version control	9
4.2	View Differences	9
5	Attaching files and model outputs	11
5.1	How to attach files?	11
5.2	What to include in the <code>files</code> argument?	11
5.3	What to include in the <code>artifacts</code> argument?	11
5.4	Where to search for the files after committing?	11
6	Tracking Datasets, Hyperparameters and Metrics	13
6.1	Dataset	13
6.2	Hyperparameters	13
6.3	Metrics	13
6.4	Reset	14
7	Comparing and Analyzing experiments	15
7.1	Sort	15
7.2	Show, Hide and Reorder columns	15
7.3	Add notes	15
7.4	View Diff between specific versions	15
7.5	Archive/Delete versions	16
7.6	Filter	16
8	Collaborating on Jovian projects	17
8.1	How to add collaborators?	17
8.2	Comment on individual code cells	17
8.3	Maintain public, secret and private notebooks	17
9	Slack Notifications	19

9.1	Connect to a Slack Workspace	19
9.2	Integration Preferences	19
9.3	Send Notifications from your script	19
10	Embed Jupyter Notebooks with Jovian.ml	21
10.1	Live Demo	21
10.2	Open up Embed modal	21
10.3	Customize options and preview	22
10.4	Copy and Embed	22
11	Jovian Pro	23
12	Commit	25
13	Log Dataset, Hyperparams & Metrics	27
14	Send Notifications to Slack	29
15	Command Line Commands	31
15.1	Initialize	31
15.2	Clone a Notebook	31
15.3	Pull the latest Notebook	31
15.4	Install the required dependencies	31
15.5	Version	32
15.6	Enable or Disable Jupyter Notebook Extension	32
16	Fastai Callback	33
17	Keras Callback	35
18	oEmbed Endpoint for embedding Jovian Notebooks	37
18.1	API Endpoint URL	37
19	Jovian: Libraries and Integrations	39
19.1	Jupyter Notebook Extension	39
19.2	Slack Integration	40
19.3	PyCharm Integration	40
19.4	Vscode Integration	40
19.5	Github Integration	40
19.6	Telegram Integration	40
19.7	Keras Integration	40
19.8	Fastai Integration	40
19.9	Tensorflow Integration	41
19.10	PyTorch Integration	41
19.11	Scikit Learn Integration	41
19.12	Xgboost Integration	41
19.13	SciPy Integration	41
19.14	OpenCV Integration	41
19.15	Apache Spark Integration	41
19.16	Anaconda Integration	41
Index		43

Jovian is an open-source Python package integrated with to provide the tools necessary for Data Scientists and ML/DL Engineers to **Track, Collaborate** and **Automate** projects where even Students and Enthusiasts can leverage the same and also use to **Share** and **Showcase** their projects.

INSTALLATION

The `jovian` python library can be installed using the `pip` package manager. To install `jovian` via terminal or command line, run:

```
pip install jovian --upgrade
```

You can also install the `jovian` library directly within a Jupyter Notebook, by running the following command in a code cell:

```
!pip install jovian --upgrade
```

Caution: If you get a `Permission denied` error, try installing with `sudo` permission (on Linux/Mac).

```
$ sudo pip install jovian --upgrade
```

Another alternative is to try installing with the `--user` flag, but you'll need to ensure that the target directory is added to your system `PATH`.

```
$ pip install jovian --upgrade --user
```

Once the installation is complete, you can start [uploading Jupyter notebooks to Jovian](#).

Configuration (for Jovian Pro users only)

If you are a [Jovian Pro](#) user, run the following commands on the terminal (or command line) to connect the `jovian` library with your company's internal Jovian Pro site:

```
jovian configure
```

You can also do this directly within a Jupyter notebook, by executing the following inside a code cell:

```
import jovian
jovian.configure()
```

The above command prompts for the following information:

1. **Organization ID:** The Organization ID provided by your company for authentication. E.g. if you are accessing Jovian Pro at <https://mycompany.jovian.ml>, your organization ID is `mycompany`.
2. **API key:** You'll get the API key when you're logged in to your organization's Jovian Pro site. By clicking on the *API key* button, the key will be copied to clipboard.

Note: You need to run `jovian configure` or `jovian.configure()` only once after installation. Your credentials are cached in the `~/ .jovian` directory on your computer. You can run `jovian reset` to clear this

configuration.

You can learn more about Jovian Pro [here](#), or start [uploading Jupyter notebooks to Jovian](#) in the next section.

UPLOADING JUPYTER NOTEBOOKS TO JOVIAN

Jovian allows you to upload and share Jupyter Notebook instantly with a single command, directly within Jupyter. Make sure you've completed the [installation](#) before reading further.

2.1 Uploading Notebooks

Step 1: Import `jovian` by running the following command within a Jupyter notebook.

```
import jovian
```

Step 2: After writing some code, running some experiments, training some models and plotting some charts, you can save and commit your Jupyter notebook.

```
jovian.commit()
```

When you run `jovian.commit` for the first time you'll be asked to provide an API key, which you can get from your Jovian.ml (or Jovian Pro) account.

Here's what `jovian.commit` does:

- It saves and uploads the Jupyter notebook to your Jovian.ml (or Jovian Pro) account.
- It captures and uploads the python virtual environment containing the list of libraries required to run your notebook.
- It returns a link that you can use to view and share your notebook with friends or colleagues.

For more features of `jovian.commit` and API reference visit [Commit](#).

Attention: In certain environments like JupyterLab and password protected notebooks, `jovian` may not be able to detect the notebook filename automatically. In such cases, pass the notebook's name as the `nb_filename` argument to `jovian.commit`.

2.2 Benefits of Jovian

Easy sharing and collaboration: Just copy the link to share an uploaded notebook with your friends or colleagues. Your notebooks are also visible on your profile page, unless you mark them *Secret*. You can also add collaborators and let others contribute to your project ([learn more](#)).

Cell-level comments and discussions: Jovian’s powerful commenting interface allows your team to discuss specific parts of a notebook with cell-level comment threads. Just hover over a cell and click the *Comment* button. You’ll receive an email when someone comments on your notebook, or replies to your comment.

End-to-end reproducibility: Jovian automatically captures Python libraries used in your notebook, so anyone (including you) can reproduce your work on any computer with a single command: `jovian clone`. You can also use the ‘Run’ dropdown on the Jovian notebook page to run your notebooks on free cloud GPU platforms like Google Colab, Kaggle Kernels and BinderHub.

This is just a small selection of features that Jovian offers. Continue reading by clicking the `Next ->` button to learn more, or use the sidebar to jump to a specific section.

REPRODUCING UPLOADED NOTEBOOKS

An uploaded notebook on Jovian.ml can be reproduced in any other machine. Following are the steps involved to reproduce a notebook.

3.1 Clone

1. Visit the link of the uploaded notebook.
2. Click on the `Clone` button, to copy the notebook's clone command to the clipboard.
3. Paste the command in the terminal, in the directory where you want to clone the notebook project and then run the command.

The copied command will be of the the following format

```
jovian clone <username/project-title>
```

3.2 Install

Jovian.ml captures the original python environment of the notebook, which make it easier to reproduce the notebook by installing all the required dependencies. The following commands uses Anaconda to install all the required packages, make sure that conda is installed.

Once the notebook is cloned, it would have created a folder with the name of the notebook project.

Move into that directory.

```
cd jovian-demo
```

Then run

```
jovian install
```

The above command prompts for a virtual environment name where it will install all the required packages. By default it will have the original environment name in the square brackets, just click `enter` key to retain the name else specify the environment name.

In this way, Jovian.ml seamlessly ensures the end-to-end reproducibility of your Jupyter notebooks across different operating systems.

Note: You have to own the notebook or have to be a collaborator to commit changes to the same notebook project. If not you can commit the cloned notebook with any changes to your Jovian profile as a new notebook project.

3.3 Pull

If there are any new versions uploaded after you have cloned the notebook by any of the collaborator. You can use `pull` to get all those changes.

Move to the cloned directory and run

```
jovian pull
```

Attention: Beware any uncommitted changes will be lost during the process of `jovian pull`. When you pull the notebook it will be a duplicate of the latest version of the notebook on Jovian.

NOTEBOOK VERSIONING AND DIFFS

4.1 Version control

If you're used to creating many duplicate versions of notebooks with slight modifications and long file names. Look no further, Jovian.ml will be your version control for notebooks.

`jovian.commit` records all the versions under same notebook project. So, each change can be a version by author and collaborators which can be easily toggled in the website

Note: You have to own the notebook or have to be a collaborator to commit changes to the same project notebook. If not you can commit any changes made to your profile as a new notebook.

4.2 View Differences

All the versions are comparable, you can view additions, deletions made among any 2 versions of the notebook and also hide/show common part of the code.

How to view the differences?

1. `Commit` different versions and visit Jovian.ml .
2. Click on `Version` drop down on the right top corner.
3. Click on `Compare Versions`
4. Select any 2 versions with the use of check boxes and click on `View Diff` button.

There are more things to be compared, but first let's add more content to the notebook to understand all the parameters that can be compared. Click on `Next` to follow through.

ATTACHING FILES AND MODEL OUTPUTS

As seen in the [previous section](#) by committing, source code and environment files are captured & uploaded. More files can be attached to the notebook such as files with helper code, output files/model checkpoints that the notebook is generating.

5.1 How to attach files?

```
jovian.commit(files=[], outputs=[])
```

5.2 What to include in the `files` argument?

The type of files which is required to run the notebook.

- Helper code (.py)
- Some input CSVs

5.3 What to include in the `artifacts` argument?

Any type of outputs that the notebook is generating.

- Saved model or weights (.h5, .pkl, .pth)
- Outputs, Submission CSVs
- Images outputs

5.4 Where to search for the files after committing?

All the attached files are listed under `Files` Tab.

Files can be:

1. Renamed
2. Downloaded
3. Deleted
4. View Raw

5. Uploaded

TRACKING DATASETS, HYPERPARAMETERS AND METRICS

Spreadsheets is one of the ways to track information & results of multiple ML experiments. However, using spreadsheets can be tiresome and non-intuitive without the context of the code.

Jovian.ml makes its easy for anyone to track information about datasets, hyperparameters and metrics which are associated with each version of the your experiment in notebooks. Its also displays these information version-by-version of your notebook under single UI.

These information of a notebook are all added to `Records Tab` where you can toggle and view each version's log.

6.1 Dataset

```
data = {
    'path': '/datasets/mnist',
    'description': '28x28 gray-scale images of handwritten digits'
}
jovian.log_dataset(data)
```

6.2 Hyperparameters

```
hyperparams = {
    'arch_name': 'cnn_1',
    'lr': .001
}
jovian.log_hyperparams(hyperparams)
```

6.3 Metrics

```
metrics = {
    'epoch': 1,
    'train_loss': .5,
    'val_loss': .3,
    'acc': .94
}
jovian.log_metrics(metrics)
```

The input to any of these can be a python dict . You can add custom parameters that are related to your experiment and have it record values manually, or automate it to record the values of a variable in a loop. Visit [this](#) page for these logging API reference.

We have callbacks for [keras](#) and [fastai](#) to automatically record hyperparams and metrics check it out.

6.4 Reset

If you're not satisfied with some experiment and want to discard the current recorded logs before a commit. Use

```
jovian.reset()
```

Click [Next](#) to look at how to compare all of these information of all the versions.

COMPARING AND ANALYZING EXPERIMENTS

Once you have more than 2 [versions](#) of a notebook, you will be able to use `Compare Versions` present in the `Version` dropdown on the top right corner.

Here you can observe all types of information about all of your versions.

- Title
- Time of Creation
- Author
- All the parameters logged under dataset.
- All the parameters logged under hyperparameters.
- All the parameters logged under metrics.
- Notes (for author and collaborators add extra notes)

7.1 Sort

You can sort any column or a sub-column (For ex: accuracy or any other metric, date of creation etc.) by clicking on the column header.

7.2 Show, Hide and Reorder columns

You can create a custom view to analyse & compare your choice of parameters. Click on `Configure` button and then tick on the checkboxes to create a customized view. Click and drag the elements to reorder them based on your preference.

7.3 Add notes

You can add notes to summarize the experiment for reference or for collaborators to refer to.

7.4 View Diff between specific versions

Select any of the 2 versions by ticking the checkbox next to each version-row of the compare table which can be seen when you hover over any row. Click on `View Diff` button to view the additions and deletion made.

7.5 Archive/Delete versions

Select version/versions by ticking the checkbox of the row/rows. This enables both `Archive` and `Delete` ready for the respective actions.

7.6 Filter

By default all the archived versions are hidden, you can display them by enabling `Show Archived in Filter` dropdown.

COLLABORATING ON JOVIAN PROJECTS

Jovian.ml allows you to add collaborators to work with you on a ML Project.

8.1 How to add collaborators?

Click on `Share` button of the notebook and add them by their username or email id registered with Jovian.ml (you can add a non jovian user email id as well to send an invite).

This will allow the contributors to be able to `commit` changes to the same notebook project. The experiments by all the collaborators will also show up in the `compare table`. tab.

8.2 Comment on individual code cells

Users can comment on any code cells individually and maintain that thread to have specific discussion about a part of the source code with context.

8.3 Maintain public, secret and private notebooks

You can find the option to `Public`, `Secret` and `Private` in the settings for each notebook.

- **Public** : These notebooks are visible on your profile and accessible to all.
- **Secret** : These notebooks are hidden from the profile but anyone with the link can access the notebook.
- **Private** : These notebooks are only accessible to the owner and collaborators.

SLACK NOTIFICATIONS

Get notifications from your training experiment and stay updated with all the milestones of your code. No more watching the progress bar of your fit function to keep track of your model training. Use the same integration to get notification about other activities on Jovian.

9.1 Connect to a Slack Workspace

Visit [Jovian.ml](#) and click on the `Connect Slack`. You'll be redirected to Slack Webpage.

Choose a workspace from the top right corner and a channel to integrate our Slack app. By clicking on `Allow` integration will be completed and will get a acknowledgement on the selected channel, this is where you'll be getting all your notifications.

Note: We suggest you to create your own [Slack Workspace](#) so that you won't spam with notifications on a public workspace.

9.2 Integration Preferences

You can customize on what notifications you get to your Slack. To update the preferences visit [Jovian.ml Integrations](#) or you go to your `Profile Dropdown` on the top right corner and click on `Integrations`.

9.3 Send Notifications from your script

This will be helpful to get updates on while training a model. You can send any `python dict` or `string`, it can be when some milestones are reached or information about the metrics.

We have this integrated to our callbacks to get automated notifications about the metrics, check out [Callbacks Section](#).

For API documentation check out [Jovian Slack Notify](#)

EMBED JUPYTER NOTEBOOKS WITH JOVIAN.ML

If you're a blogger who takes screen snips from your Jupyter Notebooks to attach to your blog or want to showcase your wonderful notebooks on a website and wondering how to embed one. We have heard your worries and are here with this feature, any notebook on Jovian.ml is embeddable.

We got you covered if you want to embed any of the following.

- Markdown cell
- Code cell with output
- Code cell without output
- Just the output cell
- or Whole Notebook

10.1 Live Demo

Before seeing how to to embed, have a preview of the embed right here. Below we have embedded a Jupyter notebook in our docs page, using iframe. You can interact with the notebook like copy the source code of a cell, copy a image output, scroll each cells etc.

10.2 Open up Embed modal

[Commit](#) a notebook or visit a uploaded notebook on Jovian.ml

10.2.1 Click on Embed button

This is ideal if you need embed the whole notebook

OR

10.2.2 Click on Embed icon on any cell

This is ideal when you need to embed a specific cell

10.3 Customize options and preview

Go ahead if u need more customization like `only output cell` and preview the embed below.

10.4 Copy and Embed

10.4.1 Copy Embed Link for sites which support oEmbed

Medium and Reddit support oEmbed so if you're writing a blog and want to add snippets with or without output charts or helping someone on reddit thread you can use this.

Just copy and paste the embed link, here is a example. Click on the image to visit the medium blog where snippets are added.

10.4.2 Copy iframe code and add it to a website

If you're building a profile website to showcase your projects or academic institution/community/meetup website making a resources page this is right for you.

Just copy and paste the iframe code in the website's code, here is a example. Click on the image to visit the a example Github Page where the whole notebook is embedded.

JOVIAN PRO

[Schedule](#) a meeting for a Demo and discussion with Aakash NS (CEO, Jovian.ml).

Please contact us at hello@jovian.ml

COMMIT

```
jovian.commit(message=None, files=[], outputs=[], environment='auto', privacy='auto', filename=None, project=None, new_project=None, git_commit=True, git_message='auto', **kwargs)
```

Uploads the current file (Jupyter notebook or python script) to

Saves the checkpoint of the notebook, captures the required dependencies from the python environment and uploads the notebook, env file, additional files like scripts, csv etc. to . Capturing the python environment ensures that the notebook can be reproduced.

Parameters

- **message** (*string, optional*) – A short message to be used as the title for this version.
- **files** (*array, optional*) – Any additional scripts(.py files), CSVs etc. that are required to run the notebook. These will be available in the files tab of the project page on Jovian.ml
- **outputs** (*array, optional*) – Any outputs files or artifacts generated from the modeling processing. This can include model weights/checkpoints, generated CSVs, output images etc.
- **environment** (*string, optional*) – The type of Python environment to be captured. Allowed options are 'conda', 'pip', 'auto' (for automatic detection) and None (to skip environment capture).
- **privacy** (*bool, optional*) – Privacy level of the project (if a new one is being created).
 - 'auto' - use account level settings. Defaults to 'public'
 - 'public' - visible on profile and publicly accessible/searchable
 - 'secret' - not on profile only accessible via the direct link
 - 'private' - only for the accessible to owner and collaborators

This argument has no effect on existing project. Change the privacy settings of a existing notebook on the webapp.

- **filename** (*string, optional*) – The filename of the current Jupyter notebook or Python script. This is detected automatically in most cases, but in certain environments like Jupyter Lab or password protected notebooks, the detection may fail and the filename needs to be provided using this argument.
- **project** (*string, optional*) – Name of the project to which the current notebook/file should be committed. Format: 'username/title' e.g. 'aakashns/jovian-example' or 'jovian-example' (username of current user inferred automatically). If the project does

not exist, a new one is created. If it exists, the current notebook is added as a new version to the existing project, if you are a owner/collaborator. If left empty, project name is picked up from the *.jovianrc* file in the current directory, or a new project is created using the filename as the project name.

- **new_project** (*bool*, *optional*) – Whether to create a new project or update the existing one. Allowed option are False (use the existing project, if a *.jovianrc* file exists, if available), True (create a new project)
- **git_commit** (*bool*, *optional*) – If True, also performs a Git commit and records the commit hash. This is applicable only when the notebook is inside a Git repository.
- **git_message** (*string*, *optional*) – Commit message for git. If not provided, it uses the *message* argument

Attention: Pass notebook's name to *filename* argument, in certain environments like Jupyter Lab and password protected notebooks sometimes it may fail to detect notebook automatically.

LOG DATASET, HYPERPARAMS & METRICS

`jovian.log_dataset (data_dict=None, verbose=True, **data_args)`

Record dataset details for the current experiment

Parameters

- **data_dict** (*dict, optional*) – A python dict to be recorded as dataset.
- **verbose** (*bool, optional*) – By default it prints the acknowledgement, you can remove this by setting the argument to False.
- ****data_args** (*optional*) – Instead of passing a dictionary, you can also pass each individual key-value pair as a argument (see example below)

Example

```
import jovian

path = 'data/mnist'
description = '28x28 images of handwritten digits (in grayscale)'

jovian.log_dataset(path=path, description=description)
# or
jovian.log_dataset({ 'path': path, 'description': description })
```

`jovian.log_hyperparams (data_dict=None, verbose=True, **data_args)`

Record hyperparameters for the current experiment

Parameters

- **data_dict** (*dict, optional*) – A python dict to be recorded as hyperparameters.
- **verbose** (*bool, optional*) – By default it prints the acknowledgement, you can remove this by setting the argument to False.
- ****data_args** (*optional*) – Instead of passing a dictionary, you can also pass each individual key-value pair as a argument (see example below)

Example

```
import jovian

jovian.log_hyperparams(arch='cnn', lr=0.001)
# or
jovian.log_hyperparams({ 'arch': 'cnn', 'lr': 0.001 })
```

`jovian.log_metrics (data_dict=None, verbose=True, **data_args)`

Record metrics for the current experiment

Parameters

- **data_dict** (*dict, optional*) – A python dict to be recorded as metrics.
- **verbose** (*bool, optional*) – By default it prints the acknowledgement, you can remove this by setting the argument to False.
- ****data_args** (*any, optional*) – Instead of passing a dictionary, you can also pass each individual key-value pair as a argument (see example below)

Example

```
import jovian
jovian.log_metrics(epochs=1, train_loss=0.5,
                  val_loss=0.3, val_accuracy=0.9)
# or
jovian.log_metrics({ 'epochs': 1, 'train_loss': 0.5 })
```

`jovian.reset (*record_types)`

Reset the tracked hyperparameters, metrics or dataset (for a fresh experiment)

Parameters ***record_types** (*strings, optional*) – By default, resets all type of records.
To reset specific type of records, pass arguments *metrics*, *hyperparams*, *dataset*

Example

```
import jovian
jovian.reset('hyperparams', 'metrics')
```


SEND NOTIFICATIONS TO SLACK

`jovian.notify(data, verbose=True, safe=False)`

Sends the data to the [Slack](#) workspace connected with your [Jovian](#) account.

Parameters

- **data** (*dict/string*) – A dict or string to be pushed to Slack
- **verbose** (*bool, optional*) – By default it prints the acknowledgement, you can remove this by setting the argument to False.
- **safe** (*bool, optional*) – To avoid raising `ApiError` exception. Defaults to False.

Example

```
import jovian

data = "Hello from the Integration!"
jovian.notify(data)
```

Important: This feature requires for your Jovian account to be connected to a Slack workspace, visit [Jovian Integrations](#) to integrate them and to control the type of notifications.

COMMAND LINE COMMANDS

15.1 Initialize

Requests for a API Key for a new user, can find the key at [Jovian](#). By clicking on API key button, key will be copied to the clipboard.

```
$ jovian init
```

15.2 Clone a Notebook

Clone a notebook form Jovian, by clicking on the Clone button of a notebook repo the whole clone command will be copied to the clipboard.

```
$ jovian clone {notebook_id}
```

15.3 Pull the latest Notebook

Pull the latest version of the notebook, use the command in a cloned repository or from a repository where you have committed to jovian.

```
$ jovian pull
```

Caution: Make sure the changes are committed if needed, pull overwrites the current notebook.

15.4 Install the required dependencies

Install all the dependencies required to the the cloned notebook, use the command in a cloned repository.

```
$ jovian install
```

Important: The above command prompts ‘ Please provide a name for the conda environment [{env_name}]: ‘

Press enter to install the dependencies to *env_name* (base env if the content of the square brackets is empty) else provide the env name in the prompt.

15.5 Version

Displays the current installed version of jovian library.

```
$ jovian version
```

15.6 Enable or Disable Jupyter Notebook Extension

By default, the jovian jupyter extension is enabled.

```
$ jovian enable-extension
```

```
$ jovian disable-extension
```

Note: The changes are observed when the webpage of the notebook is refreshed.

FASTAI CALLBACK

```
class jovian.callbacks.fastai.JovianFastaiCallback(learn: fastai.basic_train.Learner,  
                                                  arch_name=None, re-  
                                                  set_tracking=True)
```

Fastai callback to automatically log hyperparameters and metrics.

Parameters

- **learn** (*Learner*) – A learner object reference of your current model.
- **arch_name** (*string*) – A name for the model you’re training.

Example

```
from jovian.callbacks.fastai import JovianFastaiCallback  
  
jvn_cb = JovianFastaiCallback(learn, 'res18')  
learn.fit_one_cycle(5, callbacks = jvn_cb)
```

Tutorial

Visit [this](#) for a detailed example on using the keras callback, also visit the *Records* tab to see all the logs of that notebook logged by the callback.

KERAS CALLBACK

```
class jovian.callbacks.keras.JovianKerasCallback(reset_tracking=True, arch_name="",  
                                                every_epoch=False, notify=False)
```

Keras Callback to log hyperparameters and metrics during model training.

Parameters

- **reset_tracking** (*string, optional*) – Will clear previously tracked hyperparameters & metrics, and start a fresh recording. Defaults to True.
- **arch_name** (*string, optional*) – A name for the model you’re training.
- **every_epoch** (*bool, optional*) – Whether to record losses & metrics for every epoch or just the final loss & metric. Defaults to False.
- **notify** (*bool, optional*) – Whether to send notification on slack when the training ends. Defaults to False.

Example

```
from jovian.callbacks.keras import JovianKerasCallback  
  
# To record logs of every epoch and to notify on slack  
jvn_cb = JovianKerasCallback(arch_name='resnet18', every_epoch=True,  
                             ↪notify=True)  
model.fit(x_train, y_train, ..., callbacks=[jvn_cb])
```

Tutorial

Visit [this](#) for a detailed example on using the fastai callback, also visit the *Records* tab to see all the logs of that notebook logged by the callback.

OEMBED ENDPOINT FOR EMBEDDING JOVIAN NOTEBOOKS

oEmbed is an open standard to easily embed content from oEmbed providers into your site. You can use the oEmbed standard for embedding Jovian notebooks into your website, have a look at [oEmbed.com](https://oembed.com).

18.1 API Endpoint URL

You can use our API endpoint to request the embed code for public Notebooks, all responses are in json format. Replace {notebook-url} by your Jovian Notebook URL, or Jovian Viewer URL, or any raw .ipynb file URL:

- [GET]<https://jovian.ml/api/oembed.json/?url={notebook-url}&maxwidth={max-width}>

Parameters:

- **url** (*String, required*): The URL of the notebook or Jovian Viewer URL.
- **cellId** (*Integer, optional*): Index of the cell of the notebook for cell-level embeds. If no `cellId` is present, whole notebook gets embedded.
- **maxwidth** (*Integer, optional*): The maximum width of the embedded resource (optional). Note that the max-height parameter is not supported. This is because the embed code is responsive and its height varies depending on its width.

Example URLs:

- Jovian Notebook URLs
 - <https://jovian.ml/aakashns/01-pytorch-basics>
 - <https://jovian.ml/aakashns/movielens-fastai/v14>
- Jovian Viewer URLs
 - <http://jovian.ml/viewer?url={notebook-url}>
- Raw .ipynb file URL

Response:

```
{
  "title": "Jovian Viewer",
  "provider_name": "Jovian",
  "provider_url": "https://jovian.ml",
  "author_name": "Jovian ML",
  "version": "1.0",
  "type": "rich",
  "author_url": "https://github.com/JovianML",
  "height": 800,
```

(continues on next page)

(continued from previous page)

```
"width": 800,  
"html": "<iframe src='https://jovian.ml/embed?url=https%3A//jvn.storage.googleapis.  
com/gists/aakashns/5bc23520933b4cc187cfel8e5dd7e2ed/raw/  
901a9d2508bd441dbf06954c5f46bf58/movielens-fastai.ipynb' title='Jovian Viewer'  
height=800 width=800 frameborder=0 allowfullscreen></iframe>"  
}
```

JOVIAN: LIBRARIES AND INTEGRATIONS

Jovian integrates seamlessly with your favorite tools and libraries. Automate your workflow and boost your productivity.

19.1 Jupyter Notebook Extension

Now you can commit your Jupyter Notebook with to [Jovian](#) just **One Click**. Make sure you've completed the *Installation* before reading further.

19.1.1 Using Jovian Jupyter Extension

Once you have successfully installed jovian, a new button `Commit` will appear on the tool bar. When using `Commit` button for first time you'll be asked to provide an API key.

You can get the API key at [Jovian](#). Once you log in, just click on `API key` button, and the key will be copied to the clipboard.

Valid API key

If the key is valid you will be notified with the following alert.

Error with API key

If the entered API key is invalid you will get following error.

Successful Commit

Once the API key has been validated, you can start committing to [Jovian](#) by clicking `Commit` button. Once the Notebook has been committed successfully you will get the confirmation message with the link where the Jupyter Notebook has been uploaded to, you can use the copy button to get the link to share the notebook.

19.1.2 Commit Dropdown to commit with more options

This makes use of [jovian.commit's](#) parameters to enable the user to commit with preferences like secret notebook, new notebook project, to add output and artifact files

By default the parameters are derived from [jovian.commit](#), once the user changes a certain parameter they are retained.

Once the parameters are set to the need click `Commit` to the commit the notebook with these parameters set.

19.1.3 Enable or Disable the extension

By default, the Jovian Jupyter Notebook Extension is enabled to the environment where jovian is installed.

You can also disable the extension by running the following command.

```
$ jovian disable-extension
```

To Enable the Notebook Extension, when you have manually disabled it.

```
$ jovian enable-extension
```

19.2 Slack Integration

Page under Construction

19.3 PyCharm Integration

Page under Construction

19.4 Vscode Integration

Page under Construction

19.5 Github Integration

Page under Construction

19.6 Telegram Integration

Page under Construction

19.7 Keras Integration

Page under Construction

19.8 Fastai Integration

Page under Construction

19.9 Tensorflow Integration

Page under Construction

19.10 PyTorch Integration

Page under Construction

19.11 Scikit Learn Integration

Page under Construction

19.12 Xgboost Integration

Page under Construction

19.13 SciPy Integration

Page under Construction

19.14 OpenCV Integration

Page under Construction

19.15 Apache Spark Integration

Page under Construction

19.16 Anaconda Integration

Page under Construction

INDEX

C

`commit()` (*in module jovian*), 25

J

`JovianFastaiCallback` (class in `jovian.callbacks.fastai`), 33

`JovianKerasCallback` (class in `jovian.callbacks.keras`), 35

L

`log_dataset()` (*in module jovian*), 27

`log_hyperparams()` (*in module jovian*), 27

`log_metrics()` (*in module jovian*), 27

N

`notify()` (*in module jovian*), 29

R

`reset()` (*in module jovian*), 28